



ZONING PLAN



USE REGULATIONS



GENERAL USE MIX

Zoning Category		Commercial	Mixed Use Commercial	Mixed Use Residential	Residential
Zoning Code		COM	MUC	MUR	RES
Minimum required number of use type*		1	2	2	1
Use Type per Zoning Category	Commercial: <ul style="list-style-type: none">RetailOffice	✓	✓**	✓	✗
	Residential (Flats, Apartments)	✗	✓	✓*	✓
	Hospitality (Hotels, Serviced Apartments)	✓	✓	✓	✓
	Secondary/Complementary Uses (Community Facilities, Sport & Entertainment)	✓	✓	✓	✓
See details of Permitted Uses Table in page 4					

DETAILED USE SPLIT

MUC: Mixed Use Commercial	Uses Mix	GFA split		Allowed Floor Location
		Plot < 2000 sqm or for Single Tower/ Higher Building	Plot ≥ 2000 sqm or for Multiple Tower/ Higher Buildings	
Commercial**: <ul style="list-style-type: none">RetailOffice	✓	Total Com. 20% min	Total Com. 20% min	All
		Retail 40% max	Retail 40% max	Retail at ground level; podium; 1 st floor above podium; top floor level
Residential (Flats, Apartments)	✓	75% max	70% max	All
Hospitality (Hotels, Serviced Apartments)	✓		40% max	All Semi-public /publicly accessible facilities (e.g. commercial space) at ground level; podium; 1 st floor above podium; top floor level
Secondary/Complementary Uses	✓	20% max		Podium; 1 st floor above podium; top level

Uses mix: ✓ Required; ✓ Allowed; ✗ Not allowed;


* In Mixed Use Residential, the required Residential Use Type can be substituted with Hospitality Use Type (e.g. hotel, serviced apartment);

** In Mixed Use Commercial, mixing between Commercial Uses only (Retail & Office) is allowed and this already fulfils the requirement 2 mix


SPECIFIC USE REGULATIONS

Permitted uses	See Permitted Uses Table (page 4)
Recommended Uses	Type of commercial in MUC: Establishments and offices with goods or services that cater city-wide (ie. main offices) and complementary to the cultural facilities in the Downtown area
Not permitted uses	All other uses not listed in the General Permitted Uses Table (e.g. garage/car repair/heavy industry etc)
Active Frontage Uses	Percentage: For marked-sides as Active Frontages, min. 60% frontage required as Active Uses Retail, Shops, Food and Beverage (F&B), Offices, Services, Hotels, Government Offices, Clinics, Community Centres, Libraries, etc

BLOCK FORM REGULATIONS



BUILDING TYPOLOGY: ATTACHED MID RISE BUILDING & COURTYARD/ ATRIUM




BULK REGULATIONS		
Uses (as per Zoning Plan)	MUC: Mixed Use Commercial	
Height (max)	Grand Hamad (Bu Sulba) & Ali Bin Abdulla New Street	32.7 m (max)
	• G+M+7	
	Al Ashat Street	31.2 m (max)
	• G+7	
FAR (max) <i>for large plots > 2000 sqm or ≥ 10,000 sqm, refer to the Block Massing Plan and Site Planning)</i>	6.50 (along Grand Hamad/ Bu Sulba & Ali Bin Abdulla New Street)	(+ 5 % for corner lots)
	6.10 (along Al Ashat Street)	
Building Coverage (max)	80 %	
MAIN BUILDINGS		
Typology	Attached-Mid Rise with Courtyard/ Atrium	
Building Placement	Setbacks as per block plan:	
	<ul style="list-style-type: none"> • 0 m front • 0 m sides • 3 m rear 	
Build to Line <i>(a set building line on a plot, measured parallel from the front and/or corner side plot line, where the structure must be located. The building facade must be located on the build-to line)</i>	100% of 0m front setback (mandatory)	
Building Depth (max)	10 m (single-aspect building) 15 m (double-aspect building) 30 m (building with atrium) 30 m (building with integrated parking, full plot depth minimum 45 m)	
Building Size	Fine grain; 30 m maximum building width or length	
Primary Active Frontage	As indicated in the plan	
Frontage Profile	Grand Hamad & Ali Bin Abdulla & Al Ashat Street: Arcades (covered walkways): <ul style="list-style-type: none"> • 3 m minimum width (Grand Hamad & Ali Bin Abdulla Street) • 2.5 m minimum width (Al Ashat Street) • G+M maximum height • Located as per drawing 	
Basement; Half-Basement (undercroft)	<ul style="list-style-type: none"> • Allowed • 0 m setbacks • 0.5 m maximum height from street level (undercroft) 	

ANCILLARY BUILDINGS	
Height (max)	G
Setbacks	<ul style="list-style-type: none"> • 0 m sides • 3 m rear
Building Depth (max)	7.5 m
SITE PLANNING	
Plot Size for Subdivision	Minimum 400 sqm
Small Plot	<ul style="list-style-type: none"> • Minimum plot size of 400 sqm will allow to reach G+7, with provision of 1 undercroft and 1 basement for car parking. • For plot sizes < 400 m2: Allowed to be developed up to the maximum parameters set in the plan, subject to possibility of providing required parking on site
Open Space (min)	5%
Plots 2000sqm –9999sqm	<ul style="list-style-type: none"> • FAR: as stated in the Block Massing Plan • Building Coverage: 80% • Open Space: 10% min • Internal streets & utilities: 10% max
ACCESSIBILITY AND CONNECTIVITY	
Pedestrian Entry Point	As indicated in the plan
Vehicle Access Point	As indicated in the plan
Recommended Public Access on Private Plot	As indicated in the plan
PARKING	
Location	On-site parking/ undercroft/ basement/ podium parking/ Multi-Storey Car Park (MSCP) for plot size > 2000 sqm
Required Number of Spaces	As per general MSDP Car Parking Regulations
Parking Waiver	<ul style="list-style-type: none"> • 30% reduction in parking provision requirement; • Relaxation for plots ≤ 350 sqm, provided all safety measures are fulfilled as per Qatar Parking Design Manual- QPDM (refer to page 4 for details): <ol style="list-style-type: none"> 1) Allowable stall parking dimension of 2.5m x 5.5 m 2) Allowable single driveway (not ramp) provision of 3.5m width to the rear on site parking)


- All new development should follow the regulations.
- For existing buildings: the setbacks and heights are indicative, for retrofitting /alteration/ modification changes should not exceed the existing massing.
- For existing buildings which are still new and/or in good condition, it is recommended only to add the required front-part of the building (eg. light structure podium) as per indicated set back and build-to-line (which is zero setback) in the plan

LANDSCAPE & ACTIVATE CHAMFER-SIDE AT THE INTERSECTION



Provision of 'green' on the landscaped forecourt (local streets) and court-yard (ie.central/sides/rear court-yard)


Provision of green terrace roof garden (min. 50% of the area)



Activate chamfer-sides by provision of openings (windows, doors), entrance for people or landscaped gardens

RECOMMENDED ARCHITECTURAL STYLES


Qatari Contemporary*




(illustration)




WINDOW-TO-WALL RATIOS




North : 50%-60%



South : 40%-50%




East & West : 30%-40%




STANDARDS

ARCHITECTURAL STANDARD	
Architectural Theme/ Style	Qatari Contemporary Style (* Refer the details to the Townscape & Architectural Guidelines for Main Streets in Qatar)
Exterior expression	<ul style="list-style-type: none">• Clear building expression of a base, a middle and a top• The Base Part (Ground Floor): should clearly be expressed (eg. with architrave or cornice ornament)• The Middle Part:<ul style="list-style-type: none">○ Should adopt local rooted architectural language for its elements such as openings, shutters, balconies, bays etc.○ Should reveal the external expression of each storey• The Top Part should be marked by parapet or entablature
Minimum Building separation	<ul style="list-style-type: none">• 6 m between two buildings with facing non-habitable rooms• 8 m between two buildings with a facing non-habitable room and a facing habitable room• 12 m between two buildings with facing habitable rooms
Party-Wall / Common Wall	The attached building's parts should have its own wall and foundation and comply to the standard of construction and fire-safety
Floor height (maximum)	Slab to slab height (mid-point): <ul style="list-style-type: none">• Ground floor: 5 m• Ground floor with mezzanine: 6.5 m• Typical floors (residential and other): 3.50 m• Ground floor ancillary building: 3.50m
Building Orientation	<ul style="list-style-type: none">• All the facade's elements (windows, doors, balcony, bay window, etc) should respect the streets based on their hierarchy.• Primary facade should orientate to the highway /expressway/ collector/ arterial streets.
Active frontage features	Entrances, <i>madkhal</i> , lobbies, window openings, arcades, porches etc
Active chamfer at the intersection	The chamfer side should be activated by providing main access for people and designing active frontage/facade or small landscaped area with public facilities such as benches, public art, small lawn area, etc
Building Material	<ul style="list-style-type: none">• Avoid excessive use of glass-wall

	<ul style="list-style-type: none">• Use the low environmental impact materials, that conform to ISO 14025, 14040, 14044, and EN 15804 or ISO 21930
Window-to-Wall Ratios	Refer to the diagrams
LANDSCAPE STANDARD	
Forecourt	For buildings along the secondary streets, the forecourts should have small green space for landscape
Barrier/fences	Street side: not allowed Sides and rear: transparent where possible; maximum height 1.2 m
Green Roof	50% area of the podium and the roof-top should be landscaped with dominant soft-scape (trees, plants, urban farming etc)
ACCESSIBILITY STANDARD	
Pedestrian access	<ul style="list-style-type: none">• Main building entrances should be oriented to the side indicated on the plan.• Pedestrian Access on the plan indicates the side for main pedestrian access, not the approximate location
Vehicle egress and ingress	<ul style="list-style-type: none">• Main Vehicular Access on the plan indicates the side and approximate location of the access, subject to site planning and transportation constraints.
SIGNAGE	
Style	Signage should be an integral part of the building facade without background.




PARKING FORM & LOCATION OPTION



Parking at rear on small plots ≤ 350 sqm (illustration)

Conditional Requirements for Relaxation on Plots ≤ 350 sqm:

- The Owner/Developer to conduct a Parking Safety Audit as per QPDM and implement safety measures as suggested by the Safety Auditor;
- Provide exclusive signage and pavement marking cautioning the motorists and facility users (as per QPDM);
- Guidance on parking operations, accessible parking, pedestrian sidewalk to be adopted as per QPDM.
- The parking facility to be managed by trained security personnel/traffic marshal, where possible;
- Preferable use mechanical, automated, robotic parking systems, where possible;
- Use of Intelligent Transportation System technologies such as Variable Message Signage, etc, where possible.



INCENTIVE

Incentive Scheme

Provision of **Privately Owned Public Space – POPS** such *sikka*, pedestrian walkway, public plaza, pocket garden, and Community Facility:
Additional floor area of 5 m² for every 1 m² provision, up to maximum 10% of total GFA

Provision of Shared Public Parking:

Additional floor area of 50 m² for provision of each one (1) shared-car parking space, up to maximum 10% of total GFA

PERMITTED USES TABLE

Type and category		COM	MUC	MUR	RES	Code	Use
COMMERCIAL							
RETAIL	Convenience	✓	✓	✓	✓	301	Food, Beverage & Groceries Shop
	Comparison/Speciality	✓	✓	✓	✗	302	General Merchandise Store
		✓	✓	✓	✗	303	Pharmacy
		✓	✓	✓	✗	306	Electrical / Electronics / Computer Shop
		✓	✓	✓	✗	309	Apparel and Accessories Shop
	Food and Beverage	✓	✓	✓	✓	311	Restaurant
		✓	✓	✓	✓	312	Bakery
		✓	✓	✓	✓	313	Café
	Shopping Malls	✓	✓	✗	✗	314	Shopping Mall
E-charging Stations	✓	✗	✗	✗	307	E-charging Station	
OFFICE	Services/Offices	✓	✓	✓	✗	401	Personal Services
		✓	✓	✓	✗	402	Financial Services and Real Estate
		✓	✓	✓	✗	403	Professional Services
RESIDENTIAL							
	Residential	✗	✓	✓	✓	201	Residential Flats / Apartments
HOSPITALITY							
	Hospitality accommodation	✓	✓	✓	✗	2201	Serviced Apartments
		✓	✓	✓	✗	2202	Hotel / Resort
SECONDARY / COMPLEMENTARY							
COMMUNITY FACILITIES	Educational	✗	✓	✓	✓	1003	Private Kindergarten / Nurseries / Child Care Centers
		✓	✓	✓	✗	1020	Technical Training / Vocational / Language School / Centers
		✗	✓	✓	✗	1021	Boys Qur'anic School / Madrasa / Markaz
		✗	✓	✓	✗	1022	Girls Qur'anic School
	Health	✓	✓	✓	✗	1102	Primary Health Center
		✓	✓	✓	✗	1103	Private Medical Clinic
		✓	✓	✗	✗	1104	Private Hospital/Polyclinic
		✓	✓	✓	✓	1105	Ambulance Station
		✓	✓	✗	✗	1106	Medical Laboratory / Diagnostic Center
	Governmental	✗	✓	✗	✗	1201	Ministry / Government Agency / Authority
		✗	✓	✗	✗	1202	Municipality
		✓	✓	✓	✗	1203	Post Office
		✓	✓	✓	✓	1209	Library
	Cultural	✓	✓	✓	✗	1301	Community Center / Services
		✓	✓	✓	✗	1302	Welfare / Charity Facility
		✓	✓	✗	✗	1303	Convention / Exhibition Center
		✓	✓	✓	✓	1304	Art / Cultural Centers
	Religious	✓	✓	✓	✗	1406	Islamic / Dawa Center
SPORTS AND ENTERTAINMENT	Open Space & Recreation	✓	✓	✓	✓		Park - Pocket Park
		✓	✓	✗	✗	1504	Theatre / Cinema
		✓	✓	✓	✓		Civic Space - Public Plaza and Public Open Space
		✓	✓	✓	✓		Green ways / Corridors
	Sports	✗	✓	✓	✗	1607	Tennis / Squash Complex
		✗	✓	✓	✓	1609	Basketball / Handball / Volleyball Courts
		✗	✓	✓	✓		Small Football Fields
		✗	✓	✓	✓	1610	Jogging / Cycling Track
		✓	✓	✓	✓	1611	Youth Centre
		✗	✓	✓	✗	1612	Sports Hall / Complex (Indoor)
		✓	✓	✓	✓		Private Fitness Sports (Indoor)
		✓	✓	✓	✓	1613	Swimming Pool
OTHER	Special Use	✓	✓	✗	✗	2107	Immigration / Passport Office
		✓	✓	✗	✗	2108	Customs Office
	Tourism	✓	✓	✗	✗	2203	Museum

- Supporting uses serves only to the primary use should not be regarded as a separate use. Therefore, their floor area calculation should be included in the GFA of the primary use (e.g. gym facility for residents in an apartment building should be calculated in the Residential GFA, or facilities of a hotel for guests should be calculated in Hospitality GFA).
- Unlisted uses in the table are categorised as non-permitted uses, especially the hazardous/ polluted uses (e.g car repair shops, industries, polluted-workshops, etc).
- Similar uses to the permitted uses in the table will be regarded as conditional cases.